

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



(19)

(11) Publication number:

60058288 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **58166263**(51) Intl. Cl.: **C02F 1/40**(22) Application date: **08.09.83**

(30) Priority:

(43) Date of application
publication: **04.04.85**(84) Designated contracting
states:(71) Applicant: **KOBE STEEL LTD**(72) Inventor: **KITAMURA MAMORU**
YAMADA MINORU

(74) Representative:

**(54) FLOTATING SLUDGE
SCRAPING APPARATUS**

(57) Abstract:

PURPOSE: To provide the titled highly efficient apparatus capable of scraping only a high concn. sludge layer, constituted by providing a horizontal plate, which is continuously opened into water at the front or trailing end part and almost parallel to a water surface, under the rotary loci of plural buckets for scraping floated sludge by rotary driving.

CONSTITUTION: In a sludge scraping apparatus wherein a plurality of buckets 14 are attached to a water wheel type rotor supported by a truck (not shown in the drawing) running along a sludge tank 1 and sludge flowed down from each bucket 14 when each bucket 14 having floated conc. sludge scraped therein by rotation comes to the part above a rotation center is discharged by a screw feeder through the sludge charging opening 21 of a hopper, a horizontal plate 32, which is positioned under the rotary locus of the circular arc part 28 of each bucket

14 and continuously opened into water at the front or trailing end part in an advance direction shown by the arrow A and always present under the water level so as to be made almost parallel to the water surface, is attached to the above mentioned truck. By this mechanism, only high concn. sludge 33 is scraped with good efficiency without disturbing the low concn. sludge of a sludge layer.

COPYRIGHT: (C)1985,JPO&Japio

